



Model **TPF42**
Model Year **2008**
Date; June 28/06

GENERAL DESCRIPTION

Tri-axle Air Ride 35 Ton Picker Float
LENGTH APPROX 42' Over All Length
WIDTH 8 feet 6 inches Plus Pin Pockets

MAINFRAME SPECIFICATIONS

MAIN FLANGES 5/8 inch CHT 100 steel
MAIN WEB CHT 100 steel with lightening holes
CROSSMEMBERS Steel I beam on 20 inch centers

RUNNING GEAR SPECIFICATIONS

SUSPENSION Watson & Chalin TA300-15/60" sprd, rebnd chains & 5' sliding susp.
AXLES D22 77" Track with Spring brakes & Auto slacks
HUB & DRUMS 10 stud unimount cast hubs with cast iron drums
CAMS 10 spline S cam
BRAKE LINING 16 1/2 X 7
WHEELS 10 hole steel unimount 24.5 X 8.25
TIRES 11R24.5 Radial

FEATURES

PICK-UP THROAT Full width
KING PIN 2 inch on 18 inch setting
COUPLER HEIGHT 54 inch
LANDING GEAR SCONA telescoping fold-up
LIVE ROLL 7" c/w support rollers
ABS 2S1M
PIN POCKETS 7 standard per side
TIE DOWNS At every crossmember location
6 only 3 bar winches mounted down drivers side
BUMPER Heavy duty oilfield
FLOOR 2" Rough fir decking
MUDFLAPS SCONA black rubber

SYSTEMS SPECIFICATIONS

AIR SYSTEM Regulation MVSS system with scale gauge and suspension dump valve
ELECTRICAL Regulation with **LED** lights throughout except mid marker, c/w 2 sets of swing out wide load lights and a 4 prong long load light receptacle at rear.

FINISH

PAINT Sandblasted, primed and painted with Endura plastic paint