



Model : **OF1653**
Model Year **2008**

GENERAL DESCRIPTION

16 Wheel Oilfield Float 60 Ton Cap.53'

LENGTH

Approx. 53'

WIDTH

10' Plus Pin Pockets 10'4" on Susp. **upgrade to slickside**

MAINFRAME SPECIFICATIONS

MAIN FLANGES

High Tensile steel

MAIN WEB

High Tensile steel

CROSSMEMBERS

Steel I beam on 20 inch centers

RUNNING GEAR SPECIFICATIONS

SUSPENSION

Scona 100,000lb Walking Beam Susp

AXLES

D22 35 Track Axles with service chambers

HUB & DRUMS

10 Stud unimount c/w Synthetic grease packed bearings

WHEELS

24.5x8.25 Steel unimount

TIRES

11R 24.5 Radial Tires

FEATURES

PICK-UP THROAT

Full width with cable savers

KING PIN

2" solid on 18" setting

COUPLER HEIGHT

54 inch

LANDING GEAR

SCONA telescoping fold-up

LIVE ROLL

10 inch with support rollers with pin pockets on end of roll @ 45°inside end plate

CENTER ROLL

7 inch Ratcheting air lift

2nd non ratchet roll behind dolly legs

PIN POCKETS

7 standard/side, mounted in flange & 8 in front of live roll at 9'6" ,9' ,8'6" & 8'

One standard pin pocket each side in flange by center Roll

TIE DOWNS

At crossmember locations where possible

BUMPER

Heavy duty oilfield

TIRE CARRIER

Underslung on curbside

FLOOR

3 inch rough Douglas fir decking

MUDFLAPS

SCONA black rubber

BOOSTER ATT.

T/A Claw style booster hook up on rear

SYSTEMS SPECIFICATIONS

AIR SYSTEM

Regulation MVSS system

ELECTRICAL

Regulation with **LED** throughout except midmarker, 2 sets of swing out lights to 12' 6"

Controls for booster hook up on Drivers Side

OPTIONAL

Remote Grease Bank

FINISH

PAINT

Sandblasted, primed and painted one colour with Endura plastic paint