

Model: 2003 Scona Ramp Loby

General Description

Length: Tri – axle air ride 50 Ton Narrow Neck Ramp Loby
Approx 53'
Width: 10 feet
Working Deck: Approx 25'

Mainframe Specifications

Main Flanges: CHT 100 Steel
Main Web: CHT 100 Steel with Lightening holes
Crossmembers: Steel I Beam on 20 inch centers

Running Gear Specifications

Suspension: HT 300-U9 air ride with reboud chains
Axles: D22H with 89" width track
Hub & Drums: 10 stud unimount cast hubs with cast iron drums
Brake Pots: Spring
Slacks: Automatic
Cams: 10 Spline S cam
Brake Lining: 16 ½ x 7
Wheels: 10 hole unimount 22.5 x 8. 1/4
Tires: 275 / 70R22.5 Michelin XTY

Features

Neck: Narrow solid goose neck with p/u throat
Jeep Ext. Narrow jeep extension c/w rollers
Fender: Steel Fenders on neck c/w rear section removable
King Pin: 2 inch removable on 18 inch settings
Coupler Height: 54" or as required
Beavertail: Scona Beavertail with 1" Grouser Bars
Dolly Legs: Telescopic
Tie Downs: At each cross member where possible & under each outrigger
Floor: 3 inch rough fir decking including goose neck
Suspension Area: Covered in 2" Douglas Fir
Wheel Area: Wheel area open

System Specification

Air System: Regulation MVSS System with Service brakes
Electrical: Regulation with sealed beam rubber mounted lights throughout, swing out wide load lights, and 4 prong long loadlight receptable on rear.

Finish

Paint: Sandblasted, primed and painted with Endura plastic paint, and conspicuity tape

Camex Equipment Sales & Rental Inc.

