

Model: 2004 Scona Tri-Axle Loby

General Description

Tri – axle air ride 50 Ton Scissor Neck Loby

Length: Approx 53'

Width: 10 feet

Working Deck Approx 28' 9"

Mainframe Specifications

Main Flanges: High Tensile Steel

Main Web: High Tensile Steel

Crossmembers: Steel I Beam on 20 inch centers

Running Gear Specifications

Suspension: HT 300-U9 air ride with reboud chains

Axles: D22H with 89" width track

Hub & Drums: 10 stud unimount cast hubs with cast iron drums

Brake Pots: Spring

Slacks: Automatic

Cams: 10 Spline S cam

Brake Lining: 16 ½ x 7

Wheels: 10 hole unimount 22.5 x 8 1/4

Tires: 275 / 70R22.5 Michelin XTY

Features

Pick-Up Throat: Full width p/u throat, Scissor assm to pin in 3 positions

Jeep Ext. Narrow jeep extension c/w rollers

King Pin: 2 inch removable on 18 inch settings

Coupler Height 54" or as required

CentreRoll 7" non ratchet

Dolly Legs Fold Down

Rear Roll 10"

Pin Pockets 7 standard/ side, mounted outside webb in flange
6 Extra pin pockets (3 each side) on Bolster & ahead of real roll

Tie Downs At each cross member where possible & under each outrigger

Floor 3 inch rough fir decking including goose neck

Suspension Area Covered in 2" rough fi

Wheel Area Open

System Specification

Air System: Regulation MVSS System with Service brakes

Electrical: Regulation with sealed beam rubber mounted lights throughout, swing out wide load lights, and 4 prong long load light receptable on rear.

Finish

Paint : Sandblasted, primed and painted with Endura plastic paint, and conspicuity tape

Camex Equipment Sales & Rental Inc.

1301-4th Street, Nisku, Alberta Tel: (780) 955-2770 Fax: (780) 955-3735 Toll Free: 1-877-955-2770
info@camex.ca www.camex.ca

