

VACUUM TRUCKS

Combination Wash/Hydro Vac Systems

**Style: Truck Mount
Wash/Hydro Vacuum Truck
Tandem and Tri-Drive Axles**



- Combination Wash/Hydro Vac system - Code 407/412 spec.
- Hibon VTB 820 or 822 pump.
- High capacity cyclone with 12" full opening lid.
- 2" quick acting brass drain valve (heated) mounted on front head.
- 2 - 4" Betts air open/spring close valve. Aluminum camlock fittings. 1- 6" Betts discharge valve.
- Water jacketed for heat.
- Hydraulic full opening rear door assembly with 6 heavy-duty wing clamps.
- Double acting hydraulic cylinder.
- 4" pipe overturn protection and gussets.
- 1-6" exhaust and 1-6" intake
- Full length hydraulic dump subframe with 20 ton - 140" stroke 3 stage cylinder. Rear dump pivot.
- 85 gal hydraulic reservoir, hydraulic oil filter and sight glass.
- Spool valve body control of rear door, hoist and vibrator. Separate controls for wash pump (inside cabinet).
- Hydraulic vibrator assembly on the bottom of the tank.
- Full length 1/8" steel checker plate fenders, 1 1/4" tubular handrails, 4 numbered placards, 50' static ground cable, toolbox complete with rain lip.
- 6" or 8" suction boom assembly with 4' extension - hydraulic powered functions and extension.
- Electronic/hydraulic pendant controls with 25' of cable. Boom fully extends to 16'.
- Hawk or Cat wash system c/w 80' x 3/4" high pressure hose, hand gun, wand and nozzle. Hotsy burner system.
- 82 bbl, 92 bbl or as customer specifications.
- Many more options available on request.



we deliver customer specific solutions



1511 Sparrow Drive, Nisku, Alberta, Canada T9E 8H9
Tel: 780.955.2770 Fax: 780.955.3735

www.camex.com