

VACUUM SYSTEM

Domestic Sewage Trucks

Style: Truck Mounted
Vacuum Industrial Products
Sewage Vacuum Truck



- 82 bbl and custom sizes available.
- Designed to withstand 14.9 PSI internal pressure and 15 PSIG external pressure (full vacuum) non code spec.
- 2 - 4" brass lever gate valve c/w aluminum camlock fittings, and heat collars to prevent freeze up.
- 12" through 36" rear manway.
- RCF 500 Fruitland vacuum pump with hydraulic drive adapter.
- Full-length 1/8" steel checker plate assembly fender assembly with heavy-duty outriggers with reinforcements.
- 1 1/4" tubular handrails with slanted uprights for extra strength.
- Spool valve body control of vacuum pump.
- Moisture trap (secondary shut-off).
- 6" heavy-duty internal shut-off with 6" stainless steel float ball/cage assembly.
- Anti-surge baffle.
- 1 - 4" air/oil vacuum pump muffler.
- 3" blower piping, wire reinforced rubber hose and clamps.
- Glycerine filled stainless steel vacuum pressure gauge.
- Steel body deck toolbox with aluminum checkered door.
- Many more options available on request.



we deliver customer specific solutions



1511 Sparrow Drive, Nisku, Alberta, Canada T9E 8H9

Tel: 780.955.2770 Fax: 780.955.3735

www.camex.com